


34 Series

2 4 5 6 8
 1250 lbs / 565 kg



The Real MVP:
Sleek Design, Impressive
Performance & All Encompassing



Load Capacity
**1250 lbs
565 kg**

Features

- Double ball bearing raceways
- Zinc plated finish
- 5/8" diameter permanent riveted kingpin
- 1/4" cold forged steel top plate & yoke legs
- 1/2" diameter Zerk axle with lock nut



Industries and Applications

Food Service Platform Trucks
 Industrial Commercial

Caster Type	Part #
Swivel	CS
Rigid	CR
Swivel/Total Lock Brake	TL
Swivel/Top Lock Brake	TS
Swivel/Directional Lock	DL
Rigid/Top Lock Brake	TR

Bearing Options	Part #
Roller	23
Q34 Precision Ball	38
1/2 I.D. Delrin	56
3/4 I.D. Delrin	57
6203 Precision Ball	63
6204 Precision Ball	64

Options	Part #
4 Position Lock	PSL-03

Size	Bolt Pattern	Attaching Bolt Dia.	Plate
4 x 4-1/2	2-5/8 x 3-5/8 to 3 x 3	3/8	03

Wheel Dia.	Tread Wid.	Wheel Type	Load Cap.	OAH	Radius	Swivel Part #	**Bearing Options
4	2	Yoke only	1250	-	-	34 CS 420-03	-
4	2	Thermoplastic Rubber	300	5-5/8	3-5/16	34 CS 420TPR**-03	23, 38, 56, 57
4	2	Donut Thermoplastic Rubber	300	5-5/8	3-5/16	34 CS 420DPR**-03	23, 38, 56, 57
4	2	Elastic Rubber Nylon	400	5-5/8	3-5/16	34 CS 420ERN**-03	23, 38, 56, 57
4	2	Rubber Steel	400	5-5/8	3-5/16	34 CS 420RS**-03	23, 38, 56, 57
4	2	Rubber Glass-filled Nylon	400	5-5/8	3-5/16	34 CS 420RN**-03	23, 38, 56, 57
4	2	Duratek High Tech Rubber	450	5-5/8	3-5/16	34 CS 420PPR**-03	23, 38, 56, 57
4	2	Duratek Donut High Tech Rubber	450	5-5/8	3-5/16	34 CS 420DTR**-03	23, 38, 56, 57
4	2	Polyurethane Polyolefin	500	5-5/8	3-5/16	34 CS 420PPU**-03	23, 38, 56, 57
4	2	Duratough Polyurethane Polyolefin	700	5-5/8	3-5/16	34 CS 420PTU**-03	23, 38, 56, 57
4	2	HD Polyolefin	700	5-5/8	3-5/16	34 CS 420HPO**-03	23, 38, 56, 57
4	2	Polyurethane Steel	700	5-5/8	3-5/16	34 CS 420PU**-03	23, 38, 56, 57
4	2	Semi-Steel	700	5-5/8	3-5/16	34 CS 420SS**-03	23, 38, 56, 57
4	2	V-Groove	700	5-5/8	3-5/16	34 CS 420VG**-03	23, 38, 56, 57
4	2	Nylon	800	5-5/8	3-5/16	34 CS 420NY**-03	23, 38, 56, 57
4	2	Solid Polyurethane	800	5-5/8	3-5/16	34 CS 420SPU**-03	23, 38, 56, 57
4	2	Polyurethane Glass-filled Nylon	800	5-5/8	3-5/16	34 CS 420MU**-03	23, 38, 56, 57
4	2	Glass-filled Nylon	800	5-5/8	3-5/16	34 CS 420MA**-03	23, 38, 56, 57
4	2	Phenolic	800	5-5/8	3-5/16	34 CS 420PH**-03	23, 38, 56, 57
4	2	Sirius HD Donut Polyurethane Aluminum	1000	5-5/8	3-5/16	34 CS 420DUA**-03	63
4	2	HD Solid Polyurethane Glass-filled Nylon	1200	5-5/8	3-5/16	34 CS 420HU**-03	23, 38, 56, 57, 63
4	2	Ductile Steel	1250	5-5/8	3-5/16	34 CS 420DS**-03	23, 38
5	2	Yoke Only	1250	-	-	34 CS 520-03	-
5	2	Thermoplastic Rubber	350	6-1/2	3-7/8	34 CS 520TPR**-03	23, 38, 56, 57
5	2	Donut Thermoplastic Rubber	350	6-1/2	3-7/8	34 CS 520DPR**-03	23, 38, 56, 57
5	2	Elastic Rubber Nylon	450	6-1/2	3-7/8	34 CS 520ERN**-03	23, 38, 56, 57
5	2	Rubber Steel	450	6-1/2	3-7/8	34 CS 520RS**-03	23, 38, 56, 57
5	2	Rubber Glass-filled Nylon	450	6-1/2	3-7/8	34 CS 520RN**-03	23, 38, 56, 57
5	2	Duratek High Tech Rubber	500	6-1/2	3-7/8	34 CS 520PPR**-03	23, 38, 56, 57



Wheel Dia.	Tread Width	Wheel Type	Load Cap.	OAH	Radius	Swivel Part #	**Bearing Options
5	2	Duratek Donut High Tech Rubber	500	6-1/2	3-7/8	34CS520DTR**-03	23, 38, 56, 57
5	2	Polyurethane Polyolefin	600	6-1/2	3-7/8	30CS520PPU**-03	23, 38, 56, 57
5	2	Duratough Polyurethane Polyolefin	750	6-1/2	3-7/8	34CS520PTU**-03	23, 38, 56, 57
5	2	HD Polyolefin	900	6-1/2	3-7/8	34CS520HPO**-03	23, 38, 56, 57
5	2	Polyurethane Steel	1000	6-1/2	3-7/8	34CS520PU**-03	23, 38, 56, 57
5	2	Semi-Steel	1000	6-1/2	3-7/8	34CS520SS**-03	23, 38, 56, 57
5	2	V-Groove	1000	6-1/2	3-7/8	34CS520VG**-03	23, 38, 56, 57
5	2	Nylon	1000	6-1/2	3-7/8	34CS520NY**-03	23, 38, 56, 57
5	2	Solid Polyurethane	1000	6-1/2	3-7/8	34CS520SPU**-03	23, 38, 56, 57
5	2	Polyurethane Glass-filled Nylon	1000	6-1/2	3-7/8	34CS520MU**-03	23, 38, 56, 57
5	2	Glass-filled Nylon	1000	6-1/2	3-7/8	34CS520MA**-03	23, 38, 56, 57
5	2	Phenolic	1000	6-1/2	3-7/8	34CS520PH**-03	23, 38, 56, 57
5	2	Sirius HD Donut Polyurethane Aluminum	1200	6-1/2	3-7/8	34CS520DUA**-03	63
5	2	HD Solid Polyurethane Glass-filled Nylon	1250	6-1/2	3-7/8	34CS520HU**-03	23, 38, 56, 57, 63
5	2	Ductile Steel	1250	6-1/2	3-7/8	34CS520DS**-03	23, 38
6	2	Yoke Only	1250	-	-	34CS620-03	-
6	2	Thermoplastic Rubber	500	7-1/2	4-7/8	34CS620TPR**-03	23, 38, 56, 57
6	2	Donut Thermoplastic Rubber	500	7-1/2	4-7/8	34CS620DPR**-03	23, 38, 56, 57
6	2	Elastic Rubber Nylon	550	7-1/2	4-7/8	34CS620ERN**-03	23, 38, 56, 57
6	2	Rubber Steel	550	7-1/2	4-7/8	34CS620RS**-03	23, 38, 56, 57
6	2	Rubber Glass-filled Nylon	550	7-1/2	4-7/8	34CS620RN**-03	23, 38, 56, 57
6	2	Duratek High Tech Rubber	600	7-1/2	4-7/8	34CS620PPR**-03	23, 38, 56, 57
6	2	Duratek Donut High Tech Rubber	600	7-1/2	4-7/8	34CS620DTR**-03	23, 38, 56, 57
6	2	Polyurethane Polyolefin	720	7-1/2	4-7/8	34CS620PPU**-03	23, 38, 56, 57
6	2	Duratough Polyurethane Polyolefin	900	7-1/2	4-7/8	34CS620PTU**-03	23, 38, 56, 57
6	2	HD Polyolefin	1000	7-1/2	4-7/8	34CS620HPO**-03	23, 38, 56, 57
6	2	Polyurethane Steel	1200	7-1/2	4-7/8	34CS620PU**-03	23, 38, 56, 57
6	2	Semi-Steel	1200	7-1/2	4-7/8	34CS620SS**-03	23, 38, 56, 57
6	2	V-Groove	1200	7-1/2	4-7/8	34CS620VG**-03	23, 38, 56, 57
6	2	Nylon	1200	7-1/2	4-7/8	34CS620NY**-03	23, 38, 56, 57
6	2	Solid Polyurethane	1200	7-1/2	4-7/8	34CS620SPU**-03	23, 38, 56, 57
6	2	Polyurethane Glass-filled Nylon	1200	7-1/2	4-7/8	34CS620MU**-03	23, 38, 56, 57
6	2	Glass-filled Nylon	1200	7-1/2	4-7/8	34CS620MA**-03	23, 38, 56, 57
6	2	Phenolic	1200	7-1/2	4-7/8	34CS620PH**-03	23, 38, 56, 57
6	2	Sirius HD Polyurethane Aluminum	1250	7-1/2	4-7/8	34CS620TUA**-03	63
6	2	Sirius HD Donut Polyurethane Aluminum	1250	7-1/2	4-7/8	34CS620DUA**-03	63
6	2	HD Solid Polyurethane Glass-filled Nylon	1250	7-1/2	4-7/8	34CS620HU**-03	23, 38, 56, 57, 63
6	2	Ductile Steel	1250	7-1/2	4-7/8	34CS620DS**-03	23, 38
8	2	Yoke Only	1250	-	-	34CS820-03	-
8	2	Thermoplastic Rubber	600	9-1/2	6-1/2	34CS820TPR**-03	23, 38, 56, 57
8	2	Donut Thermoplastic Rubber	600	9-1/2	6-1/2	34CS820DPR**-03	23, 38, 56, 57
8	2	Elastic Rubber Nylon	600	9-1/2	6-1/2	34CS820ERN**-03	23, 38, 56, 57
8	2	Rubber Steel	600	9-1/2	6-1/2	34CS820RS**-03	23, 38, 56, 57
8	2	Rubber Glass-filled Nylon	600	9-1/2	6-1/2	34CS820RN**-03	23, 38, 56, 57
8	2	Duratek High Tech Rubber	675	9-1/2	6-1/2	34CS820PPR**-03	23, 38, 56, 57
8	2	Duratek Donut High Tech Rubber	675	9-1/2	6-1/2	34CS820DTR**-03	23, 38, 56, 57
8	2	Polyurethane Polyolefin	800	9-1/2	6-1/2	34CS820PPU**-03	23, 38, 56, 57
8	2	Duratough Polyurethane Polyolefin	1000	9-1/2	6-1/2	34CS820PTU**-03	23, 38, 56, 57
8	2	HD Polyolefin	1200	9-1/2	6-1/2	34CS820HPO**-03	23, 38, 56, 57
8	2	Polyurethane Steel	1250	9-1/2	6-1/2	34CS820PU**-03	23, 38, 56, 57
8	2	Semi-Steel	1250	9-1/2	6-1/2	34CS820SS**-03	23, 38, 56, 57
8	2	V-Groove	1250	9-1/2	6-1/2	34CS820VG**-03	23, 38, 56, 57
8	2	Nylon	1250	9-1/2	6-1/2	34CS820NY**-03	23, 38, 56, 57
8	2	Solid Polyurethane	1250	9-1/2	6-1/2	34CS820SPU**-03	23, 38, 56, 57
8	2	Polyurethane Glass-filled Nylon	1250	9-1/2	6-1/2	34CS820MU**-03	23, 38, 56, 57
8	2	Glass-filled Nylon	1250	9-1/2	6-1/2	34CS820MA**-03	23, 38, 56, 57
8	2	Phenolic	1250	9-1/2	6-1/2	34CS820PH**-03	23, 38, 56, 57
8	2	Sirius HD Polyurethane Aluminum	1250	9-1/2	6-1/2	34CS820TUA**-03	63, 64
8	2	Sirius HD Donut Polyurethane Aluminum	1250	9-1/2	6-1/2	34CS820DUA**-03	63, 64
8	2	HD Solid Polyurethane Glass-filled Nylon	1250	9-1/2	6-1/2	34CS820HU**-03	23, 38, 56, 57, 63
8	2	Ductile Steel	1250	9-1/2	6-1/2	34CS820DS**-03	23, 38