

PO | DPO



PO | DPO Polyolefin & Donut Tread Polyolefin



Features

- 70 (±5) Durometer Shore (D)
- Economic and light weight injection molded wheel
- Resistant to high shock, impact, chemicals and abrasion
- Resists water

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Black Part #	White Part #
2	7/8	1	100	1/4	278PO80B	-
2-1/2	7/8	1	100	1/4	2578PO80B	-
3	7/8	1	100	1/4	378PO80B	-
3	1	1-1/8	125	5/16	310PO81B	-
3	1-1/4	1-9/16	250	3/8	314PO82B	-
3	1-1/4	1-9/16	300	1/2	-	314DPO83E
3-1/2	1-1/4	1-9/16	325	3/8	3514DPO82B	-
4	1	1-1/8	140	5/16	410PO81B	-
4	1-1/4	1-9/16	300	3/8	414PO82B	-
4	1-1/4	1-9/16	350	3/8, 1/2	414DPO82B	414DPO83E
5	1	1-1/8	145	5/16	510PO81B	-
5	1-1/4	1-9/16	325	3/8	514PO82B	-
5	1-1/4	1-9/16	375	3/8, 1/2	514DPO82B	514DPO83E
5	2	2-3/16	600	3/4	520PO88B	520PO88E
6	1-1/2	1-5/8	650	1/2	615PO83B	-
6	2	2-3/16	700	3/4	-	620PO88E
8	2	2-3/16	800	3/4	-	820PO88E