

SS

800° F  
-45° F3000 lbs  
1360 kg

## SS Semi-Steel

3000 lbs  
1360 kg800° F  
-45° F

### Features

- High capacity
- Use metal only bearing components for temps higher than 180°
- Zerk fitting

### Bearing Options

### Part #

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26
1/2 Q34 Precision Ball	38
3/4 Double Groove Precision	39D
1 Double Groove Precision	40D

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller	*Precision Ball
3	1-1/4	1-3/8	350	3/8, 1/2	314SS*	82, 83	-	-
4	1-1/4	1-1/2	425	3/8, 1/2	414SS*	82, 83	-	-
4	2	2-3/16	700	1-3/16	420SS*	84	23	38
5	2	2-3/16	1000	1-3/16	520SS*	84	23	38
6	2	2-3/16	1200	1-3/16	620SS*	84	23	38
6	2-1/2	2-3/4	1800	1-15/16	625SS*	86	25, 26	-
6	3	3-1/4	2500	1-15/16	630SS*	86	25, 26	39D, 40D
8	2	2-3/16	1400	1-3/16	820SS*	84	23	38
8	2-1/2	2-3/4	1800	1-15/16	825SS*	86	25, 26	-
8	3	3-1/4	2500	1-15/16	830SS*	86	25, 26	39D, 40D
10	2-1/2	2-3/4	2000	1-15/16	1025SS*	86	25, 26	-
10	3	3-1/4	3000	1-15/16	1030SS*	86	25, 26	39D, 40D
12	2-1/2	2-3/4	2000	1-15/16	1225SS*	86	25, 26	-
12	3	3-1/4	3000	1-15/16	1230SS*	86	25, 26	39D, 40D