


VG V-Groove



Features

- V-groove wheels are precision machined 90° with 7/8" relief groove
- Use metal only bearing components for temps higher than 180°
- Zerk fitting

Bearing Options	Part #
3/4 Roller	23
1 Roller	25
1-1/4 Roller	26
1/2 Q34 Precision Ball	38
3/4 Double Groove Precision	39D
1 Double Groove Precision	40D

Wheel Dia.	Tread Width	Hub Length	Load Cap.	Plain Bore Dia.	Part #	*Plain Bore	*Roller	*Precision Ball
4	1-1/2	1-5/8	350	1-3/16	415VG*	84	23	38
4	2	2-3/16	700	1-3/16	420VG*	84	23	38
5	2	2-3/16	1000	1-3/16	520VG*	84	23	38
6	2	2-3/16	1200	1-3/16	620VG*	84	23	38
6	2-1/2	2-3/4	1800	1-15/16	625VG*	86	25, 26	-
6	3	3-1/4	2500	1-15/16	630VG*	86	25, 26	39D, 40D
8	2	2-3/16	1400	1-3/16	820VG*	84	23	38
8	2-1/2	2-3/4	1800	1-15/16	825VG*	86	25, 26	-
8	3	3-1/4	2500	1-15/16	830VG*	86	25, 26	39D, 40D
10	3	3-1/4	3000	1-15/16	1030VG*	86	25, 26	39D, 40D
12	3	3-1/4	3000	1-15/16	1230VG*	86	25, 26	39D, 40D